


Main ratings


Drain-source voltage $V_{DS} = 50\text{ V}$
 Continuous drain current $I_D = 39\text{ A}$
 Drain-source on-resistance $R_{DS(on)} = 0,04\ \Omega$

N-Channel



Description SIPMOS, N-channel, enhancement mode
Case Metal case 3A2 in accordance with DIN 41872, or TO 204 AE (TO 3) in accordance with JEDEC. Approx. weight 12 g

Type	Ordering code
BUZ 14	C67078-A1000-A2



Dimensions in mm

Maximum ratings

Description	Symbols	Ratings	Units	Conditions
Drain-source voltage	V_{DS}	50	V	
Drain-gate voltage	V_{DGR}	50	V	$R_{GS} = 20\text{ k}\Omega$
Continuous drain current	I_D	39	A	$T_C = 25\text{ }^\circ\text{C}$
Pulsed drain current	I_{Dpuls}	155	A	$T_C = 25\text{ }^\circ\text{C}$
Gate-source voltage	V_{GS}	± 20	V	
Max. power dissipation	P_D	125	W	$T_C = 25\text{ }^\circ\text{C}$
Operating and storage temperature range	T_J T_{stg}	$-55 \dots +150$	$^\circ\text{C}$	
DIN humidity category	C			DIN 40040
IEC climatic category	55/150/56			DIN IEC 68-1

Thermal resistance

Chip - case	R_{thJC}	$\leq 1,0$	K/W
Chip - ambient	R_{thJA}	≤ 35	K/W

184 Preferred Type

0766 F-05

Electrical characteristics(at $T_j = 25^\circ\text{C}$ unless otherwise specified)

Description	Symbol	Characteristics			Unit	Conditions
		min.	typ.	max.		

Static ratings

Drain-source breakdown voltage	$V_{(BR)DSS}$	50	65	—	V	$V_{GS} = 0V$ $I_D = 0,25mA$
Gate threshold voltage	$V_{GS(th)}$	2,1	3,0	4,0		$V_{DS} = V_{GS}$ $I_D = 1mA$
Zero gate voltage drain current	I_{DSS}	—	20	250	μA	$T_j = 25^\circ C$ $T_j = 125^\circ C$ $V_{DS} = 50V$ $V_{GS} = 0V$
Gate-source leakage current	I_{GSS}	—	10	100	nA	$V_{GS} = 20V$ $V_{DS} = 0V$
Drain-source on-resistance	$R_{DS(on)}$	—	0,035	0,04	Ω	$V_{GS} = 10V$ $I_D = 22A$

Dynamic ratings


Forward transconductance	g_{fs}	7,0	18,0	—	S	$V_{DS} = 25V$ $I_D = 22A$
Input capacitance	C_{iss}	—	1600	2100	pF	$V_{GS} = 0V$ $V_{DS} = 25V$ $f = 1MHz$
Output capacitance	C_{oss}	—	1300	2000		
Reverse transfer capacitance	C_{rss}	—	500	800		
Turn-on time t_{on} ($t_{on} = t_{d(on)} + t_r$)	$t_{d(on)}$	—	30	45	ns	$V_{CC} = 30V$ $I_D = 3A$ $V_{GS} = 10V$ $R_{GS} = 50\Omega$
	t_r	—	110	170		
Turn-off time t_{off} ($t_{off} = t_{d(off)} + t_f$)	$t_{d(off)}$	—	330	430		
	t_f	—	250	330		

Reverse diode


Continuous reverse drain current	I_{DR}	—	—	39	A	$T_C = 25^\circ C$
Pulsed reverse drain current	I_{DRM}	—	—	155		
Diode forward on-voltage	V_{SD}	—	1,5	2,2	V	$I_F = 2 \times I_{DR}$ $V_{GS} = 0V, T_j = 25^\circ C$
Reverse recovery time	t_{rr}	—	150	—	ns	$T_j = 25^\circ C$
Reverse recovery charge	Q_{rr}	—	1,0	—	μC	$I_F = I_{DR}$ $d_{F/dt} = 100A/\mu s$ $V_R = 30V$

SIEMENS AKTIENGESELLSCHAFT


Power dissipation $P_D = f(T_C)$




Typical output characteristics $I_D = f(V_{DS})$
parameter: 80 μ s pulse test,
 $T_J = 25^\circ\text{C}$



Safe operating area $I_D = f(V_{DS})$
parameter: $D = 0.01$, $T_C = 25^\circ\text{C}$




Typical transfer characteristic $I_D = f(V_{GS})$
parameter: 80 μ s pulse test,
 $V_{DS} = 25\text{V}$, $T_J = 25^\circ\text{C}$



SIEMENS AKTIENGESELLSCHAFT


Typical drain-source on-state resistance

$R_{DS(on)} = f(I_D)$
 parameter: $V_{GS} = 7.5V, T_j = 25^\circ C$




Drain-source on-state resistance

$R_{DS(on)} = f(T_j)$
 parameter: $I_D = 22A, V_{GS} = 10V$
 (spread)




Typical transconductance $g_{fs} = f(I_D)$

parameter: 80 μs pulse test,
 $V_{DS} = 25V, T_j = 25^\circ C$




Gate threshold voltage $V_{GS(th)} = f(T_j)$


parameter: $V_{DS} = V_{GS}, I_D = 1mA$
 (spread)



Typical capacitances $C = f(V_{GS})$
parameter: $V_{GS} = 0, f = 1\text{MHz}$




Continuous drain current $I_D = f(T_C)$
parameter: $V_{GS} \geq 10\text{V}$




Forward characteristic of reverse diode

$I_F = f(V_{SD})$
parameter: $T_j, t_p = 80 \mu\text{s}$
(spread)



SIEMENS AKTIENGESELLSCHAFT

Transient thermal impedance $Z_{thJC} = f(t)$
 parameter: $D = t_p/T$



Typical gate-charge $V_{GS} = f(Q_{Gate})$
 parameter: $I_D \text{ puls} = 67,5A$

